



## MxPURLIN (Z)

SIZE	H	B	C	Thickness	Input width base on 2mm/R2
Z100	100	50	15	1.6-2.0	226
Z160	160	60	15	1.6-2.0	296
Z180	180	60	18	1.6-2.0	329
Z220	220	78	20	2.0-3.0	404
Z200	200	70	20	2.0-3.0	368
Z250	250	70	20	2.0-3.0	418
Z300	300	80	20	2.0-3.0	491

### ISSUED FOR APPROVAL

SENT ON \_\_\_\_\_ IN ORDER TO SCHEDULE THIS PROJECT IN THE MOST EFFICIENT MANNER, RETURN THESE DOCUMENTS, MARKED WITH YOUR COMMENTS, WITHIN ONE WEEKS FROM THE ABOVE MENTIONED DATE. ANY CHANGES MADE AFTER APPROVAL OF THESE DRAWINGS MAY DELAY THE FABRICATION AND DELIVERY PROCESS.

- APPROVED  
NO CHANGES. PROCEED WITH FABRICATION.
- APPROVED AS NOTED  
FABRICATION MAY PROCEED ON THE BASIS OF CORRECTIONS INDICATED. RESUBMIT AFTER INCORPORATING THE COMMENTS FOR RECORD.
- RESUBMIT AFTER INCORPORATING THE COMMENTS FOR REAPPROVAL.

REVIEWED BY: \_\_\_\_\_  
NAME: \_\_\_\_\_  
SIGNATURE WITH STAMP: \_\_\_\_\_ DATE: \_\_\_\_\_

REV	REVISIONS	DRAWN	CHK BY	DATE

**NOTE:-**

- IF ANY OPENING / CUTOUTS IN ROOF / WALL CLADDING COMES AT LATER STAGE OTHER THAN SHOWN IN THE DRAWINGS WILL BE EXECUTED AT EXTRA COST.
- SILICONE SEALANT WILL BE USED TO SEAL THE LENGTH WISE JOINTS OF SHEETS & FLASHINGS.
- ALL FASTENERS / SCREWS ARE STANDARD CONFIRMING TO BE AS PER TENDER
- TOP SHEET - CLADDING SHEET
  - MAKE - -
  - PROFILE - -
  - THICKNESS - -
  - SPECIFICATION - -
  - COLOR - -
- FLASHING: AS MENTIONED IN DRAWING WITH THE SAME SPECIFICATION OF ROOF / WALL CLADDING SHEETS.
- ⊙ DENOTES COLOR SIDE

**CLIENT:**  
M/s. - - - -

**Architect:**  
M/s. - - - -

**PROJECT:**  
M/s. - - - -

**PRIME CONTRACTOR:**  
M/s. - - - -

**Building:** - - - -

**Drawing Title:** MxPURLIN ("Z")

**MAXROOF**

MAX ROOFING SYSTEMS PVT. LTD.  
E-MAIL: design@maxroof.in, contact@maxroof.in  
WEBSITE: www.maxroof.in  
OFFICE: 84/6, FIFTH FLOOR, PUNE PURPLE SQUARE,  
KALWAJEERHATA, KASAPATE WASTE, WAKAD PUNE - 411 057  
CONTACT: 020-27574330 / 844028 / 844118 / 844119 / 844120

SCALE:	N.T.S.
DRG. NO.:	06
DATE:	14-04-2014
DRN BY:	SNEHA
CHK BY:	---
REV. NO.:	R0